

Specification

	HEATON VELOUR				HEATON LOOP				
<i>Construction</i>	BS4223	1/10th gauge tufted cut pile graphics			1/10th gauge tufted loop pile graphics				
<i>Pile yarn</i>	BS4407	90% Polypropylene 10% Solution Dyed Nylon			90% Polypropylene 10% Solution Dyed Nylon				
<i>Width</i>	BS3655	4m			4m				
<i>Finished pile weight</i>	BS4223	750 gms/m ²		(±5%)	750 gms/m ²			(±5%)	
<i>Pile height above backing</i>	BS4223	5 mm		(±0.5mm)	4.5 mm			(±0.5mm)	
<i>Primary backing</i>		Woven polypropylene			Woven polypropylene				
<i>Secondary backing</i>		Impervious Gel		Actionbac	Impervious Gel			Actionbac	
<i>Total carpet weight</i>	BS4223	2150 gms/m ²	(±10%)	1850 gms/m ²	(±10%)	2150 gms/m ²	(±10%)	1850 gms/m ²	(±10%)
<i>Total carpet thickness</i>	BS4223	7 mm	(±1mm)	7 mm	(±1mm)	6.5 mm	(±1mm)	6.5 mm	(±1mm)

Performance

<i>Wear classification</i>	Heavy use areas	Heavy use areas
----------------------------	-----------------	-----------------

Properties

<i>Electrostatic</i>	ISO/TR 6356	< 2kV @ 25% RH (pass) Permanently antistatic	< 2kV @ 25% RH (pass) Permanently antistatic
<i>Flammability</i>	BS4790/BS5287	Pass, low radius of effect of ignition	Pass, low radius of effect of ignition
<i>Light fastness</i>	BS1006	6 (1-8)	6 (1-8)
<i>Rubbing fastness</i>	BS1006	3-4 (1-5)	3-4 (1-5)
<i>Colour fastness to shampoo</i>	BS1006	5 (1-5)	5 (1-5)
<i>Impermeability</i>		Tested by RBI (Europe) Ltd and found to be totally impervious	Tested by RBI (Europe) Ltd and found to be totally impervious
<i>Standard treatment</i>		Fluorocarbon	Fluorocarbon
<i>Special</i>		Other backing options available - please refer to factory	Other backing options available - please refer to factory

General Information

Colour

Due to limitations in the manufacturing process, colour may vary from batch to batch.

Installation

The method of installation should conform to BS5325. The subfloor should be dry, smooth, clean and level and any defects should be made good before laying. For installations requiring more than one width, consideration should be given to seam locations as pattern matching cannot be guaranteed.

Maintenance

Vacuum for normal day to day cleaning. Spills and stains must be removed as part of a comprehensive maintenance plan including the use of dry or hot water extraction methods when required, depending upon local conditions.

Drury Lane products will provide maximum performance if installed and maintained as recommended in our installation and maintenance schedules, available on request.

We reserve the right to change technical specifications without prior notice.

Express samples

Additional samples are available for next day delivery upon request.