

Specification

Construction	BS4223	5/32" gauge loop pile	
Pile yarn	BS4407	100% solution dyed Nylon	
Width	BS3655	4m	
Finished pile weight	BS4223	660 gms/m ²	(± 5%)
Pile height above backing	BS4223	4.5 mm	(± 0.5mm)
Primary backing		Woven polypropylene	
Secondary backing		Actionbac	
Backing options		Alternative backings are available for a minimum making. Further details from the factory.	
Total carpet weight	BS4223	1550 gms/m ²	(± 10%)
Total carpet thickness	BS4223	7.5 mm	(± 1mm)

Performance

Wear classification	Heavy contract
---------------------	----------------

Properties

Electrostatic	ISO/TR 6356 IBM/ICL	< 2kV @ 25% RH (pass) Pass
Flammability	BS4790/BS5287	Pass, low radius of effect of ignition
Light fastness	BS1006	6 (1-8)
Rubbing fastness	BS1006	4-5 (1-5)
Colour fastness to shampoo	BS1006	4-5 (1-5)
Castor chair		Suitable

General Information

We reserve the right to change technical specifications without prior notice.

Colour

Due to limitations in the manufacturing process, colour may vary from batch to batch.

Installation

The method of installation should conform to BS5325. The subfloor should be dry, smooth, clean and level and any defects should be made good before laying. For installations requiring more than one width, consideration should be given to seam locations, as pattern matching cannot be guaranteed.

Maintenance

Vacuum for normal day to day cleaning. Spills and stains must be removed as part of a comprehensive maintenance plan including the use of dry or hot water extraction methods when required, depending upon local conditions.

Drury Lane products will provide maximum performance if installed and maintained in accordance with the recommendations set out in our installation and maintenance schedules, available on request.

Express samples

Additional samples are available for next day delivery upon request.