

## Specification

## THE WILSDEN COLLECTION

<i>Construction</i>	BS4223	1/10th gauge tufted cut pile graphics			
<i>Pile yarn</i>	BS4407	100% Meraklon Polypropylene heat-set fris�			
<i>Width</i>	BS3655	4m			
<i>Finished pile weight</i>	BS4223	1210 gms/m <sup>2</sup>		(±5%)	
<i>Pile height above backing</i>	BS4223	7.0 mm		(±0.5mm)	
<i>Primary backing</i>		Woven polypropylene			
<i>Secondary backing</i>		Fully impervious foam	Actionbac		
<i>Total carpet weight</i>	BS4223	2500 gms/m <sup>2</sup>	(± 10%)	2100 gms/m <sup>2</sup>	(± 10%)
<i>Total carpet thickness</i>	BS4223	9 mm	(± 1mm)	9 mm	(± 1mm)

## Performance

*Wear classification* Heavy use areas

## Properties

<i>Electrostatic</i>	ISO/TR 6356	< 2kV @ 25% RH (pass) Permanently antistatic			
<i>Flammability</i>	BS4790/BS5287	Pass, low radius of effect of ignition			
<i>Light fastness</i>	BS1006	6 (1-8)			
<i>Rubbing fastness</i>	BS1006	5 wet, 5 dry (1-5)			
<i>Colour fastness to shampoo</i>	BS1006	5 (1-5)			
<i>Impermeability</i>		Tested by RBI (Europe) Ltd and found to be totally impervious			
<i>Special</i>		Fluorocarbon treated			
		Other backing options available - please refer to factory			

## General Information

We reserve the right to change technical specifications without prior notice.

### *Colour*

Due to limitations in the manufacturing process, colour may vary from batch to batch.

### *Installation*

The method of installation should conform to BS5325. The subfloor should be dry, smooth, clean and level and any defects should be made good before laying. For installations requiring more than one width, consideration should be given to seam locations, as pattern matching cannot be guaranteed.

### *Maintenance*

Vacuum for normal day to day cleaning. Spills and stains must be removed as part of a comprehensive maintenance plan including the use of dry or hot water extraction methods when required, depending upon local conditions.

Drury Lane products will provide maximum performance if installed and maintained in accordance with the recommendations set out in our installation and maintenance schedules, available on request.

## Express samples

Additional samples are available for next day delivery upon request.